

# A fully fuzzy centralized resource allocation model using lexicographic multi-objective DEA

R. Fallahnejad, Sh. Soofizadeh\*

**Receive:** 3 September 2025;

**Accepted:** 6 December 2025

**Abstract** Effective resource allocation by a central authority is often hampered by data imprecision and uncertainty. This study develops a novel Fully Fuzzy Centralized Data Envelopment Analysis (FFCDEA) framework, designed to empower a Central Decision-Making Unit (CDM) to evaluate and simultaneously optimize the performance of all Decision-Making Units (DMUs). The proposed model extends the non-radial Enhanced Russell Measure (ERM) into a fully fuzzy environment and is structured as a lexicographic multi-objective linear program (LMOLP) to effectively handle the inherent uncertainty in input and output data, which are modeled as triangular fuzzy numbers. The inherent fractional nature of the model is linearized using the Charnes-Cooper (C-C) Transformation, rendering it readily solvable. A real-world application on 14 bank branches validates the model's practical utility, demonstrating its capability to derive specific, actionable targets for both individual branches and the system as a whole. By systematically handling data ambiguity and optimizing performance from a holistic, system-wide perspective, our FFCDEA model provides a more robust and realistic tool for strategic planning compared to traditional centralized or fuzzy DEA approaches.

**Keyword:** Data Envelopment Analysis, Lexicographic Multi-Objective Linear Programming, Centralized Resource Allocation, Fuzzy Mathematical Programming.

## 1 Introduction

### 1.1 From independent evaluation to centralized resource allocation

Efficiency assessment has long been a central topic in performance evaluation. Following Farrell's [1] foundational concepts of productive efficiency, Charnes et al. [2] developed the well-known CCR model, which revolutionized the evaluation of decision-making units (DMUs) with multiple inputs and outputs. Traditional DEA models inherently assume that DMUs operate independently and aim to maximize their own individual efficiency. However, in centralized systems—where a central authority oversees all units and allocates shared resources—this assumption is unrealistic and often leads to sub-optimal system-wide performance.

To address this, researchers shifted their focus toward Centralized DEA (CDEA) models. Golany et al. [3] and Athanassopoulos [4] were among the first to propose frameworks for

---

\* Corresponding Author. (✉)

E-mail: [shsoofizadeh@tvu.ac.ir](mailto:shsoofizadeh@tvu.ac.ir) (SH. Soofizadeh)

**R. Fallahnejad**

Department of Mathematics, Khor.C., Islamic Azad University, Khorramabad, Iran

**SH. Soofizadeh**

Department of Basic Sciences, Technical and Vocational University (TVU), Tehran, Iran.

system-wide efficiency and central grant allocation, though early models faced computational and feasibility limitations. A significant breakthrough was made by Lozano and Villa [5, 6], who introduced radial and non-radial CDEA models under variable returns to scale. Their models aimed to optimize total resource consumption and output production simultaneously from a macroeconomic perspective. This foundation sparked a series of methodological advancements in CDEA. Subsequent studies expanded centralized frameworks to include BCC models [7], enhanced Russell measures [8], and simplified linear structures [9]. More recently, researchers have tailored CDEA to address complex structural constraints, such as step-by-step improvement paths [10], bi-level optimization structures enforcing minimum individual efficiency [11], comprehensive target-setting mechanisms [12], and directional distance models for equitable grant allocation [13]. In practical applications, CDEA has proven highly effective in sectors requiring strict centralized supervision, such as banking [14].

## 2.2 Managing uncertainty through fuzzy DEA

While classical and centralized DEA models provide robust analytical tools, they fundamentally rely on deterministic data. Real-world applications, however, are frequently plagued by missing, random, or imprecise data often expressed in qualitative terms. Ignoring such uncertainty can severely distort efficiency scores and mislead decision-makers. To capture this ambiguity, Bellman and Zadeh's [15] fuzzy set theory was integrated into DEA, pioneering the field of Fuzzy DEA (FDEA).

Since Sengupta [16] first incorporated fuzzy constraints into DEA based on Zimmermann's optimization principles [17], a wide array of FDEA methodologies has emerged. Researchers have developed diverse techniques to handle imprecise inputs and outputs, including efficiency membership functions [18], fuzzy expected values [19], and fuzzy arithmetic for determining efficiency bounds [20]. To improve discrimination among DMUs in fuzzy environments, several ranking approaches [21-23] and methods for controlling weight flexibility [24, 25] have been proposed. Furthermore, the application of FDEA has expanded into complex network structures, such as two-stage series systems [26, 27], and real-world problems like real estate risk evaluation [28], transportation route selection [29], healthcare efficiency [30], and circular economy performance [31]. More advanced techniques have also incorporated game theory [32], Pythagorean fuzzy sets [33], and multi-objective lexicographic approaches [34] to better align efficiency evaluations with managerial preferences.

## 2.3 Research gap and contribution

Despite the extensive literature on both Centralized DEA and Fuzzy DEA, the intersection of these two domains remains relatively sparse. Centralized resource allocation inherently involves long-term strategic planning, making it highly susceptible to uncertainty. While some recent studies have begun to explore centralized allocation under ambiguity [35], or have proposed hybrid robust-fuzzy approaches [36] and fully fuzzy multi-objective programming for independent units [37, 38], a comprehensive framework that addresses fully fuzzy centralized resource allocation using a multi-objective lexicographic approach is lacking.

Most existing CDEA models either treat data as crisp or apply overly simplified fuzzy conversions that lose vital information. This study aims to bridge this gap. By developing a Fully Fuzzy Centralized DEA (FFCDEA) model utilizing a lexicographic optimization strategy,

this research provides decision-makers with a reliable, step-by-step tool to allocate resources and set targets system-wide, while mathematically preserving the inherent uncertainties of real-world operational environments.

The remainder of this paper is organized as follows: Section 2 introduces the preliminaries, including basic fuzzy arithmetic and foundational DEA concepts. Section 3 details the development of the proposed FFCDEA framework, explicitly outlining the C-C Transformation and the lexicographic multi-objective optimization procedure. Section 4 presents a comprehensive real-world application involving 14 bank branches. This section demonstrates the computational procedure, evaluates both systemic and DMU-level efficiency targets, and extensively discusses the managerial implications and practical considerations of resource reallocation. Finally, Section 5 concludes the paper and outlines potential directions for future research. Additionally, extended datasets for different fuzzy bounds and the computational codes ensuring full reproducibility are provided as Supplementary Materials/Appendices.

## 2 Preliminaries

This section provides the foundational concepts and mathematical background necessary for developing the proposed methodology. To ensure clarity and consistency throughout the paper, we first present a comprehensive nomenclature defining all indices, parameters, and variables used in our models. Following this, the section is divided into four main parts: First, we review the basic principles of DEA, with a specific focus on the Russell measure. Second, we discuss the centralized resource allocation model and its equivalent linear transformation based on recent developments in the literature. Third, essential concepts from fuzzy set theory, particularly triangular fuzzy numbers (TFNs) and their arithmetic operations, are introduced to handle data uncertainty. Finally, we explain the fundamentals of the lexicographic multi-objective programming approach in a fuzzy context, which serves as the core computational engine for our proposed framework.

### 2.1 DEA and the ERM

DEA is a widely used non-parametric approach for evaluating the relative efficiency of a set of homogeneous DMUs. Suppose we have  $n$  DMUs, where each DMU <sub>$j$</sub>  ( $j = 1, \dots, n$ ) consumes  $m$  inputs to produce  $s$  outputs. Let  $x_{ij}$  denote the  $i$ -th input ( $i = 1, \dots, m$ ) and  $y_{kj}$  denote the  $k$ -th output ( $k = 1, \dots, s$ ) of DMU <sub>$j$</sub> . Furthermore, let  $X$  and  $Y$  represent the input and output matrices of all DMUs, respectively. Assuming a VRS technology, the Production Possibility Set (PPS), denoted by  $T_v$ , is defined as follows:

$$T_v = \{ (x, y) \mid x \geq X\lambda, y \leq Y\lambda, \sum_{j=1}^n \lambda_j = 1, \lambda_j \geq 0, j = 1, \dots, n \}$$

where  $\lambda = (\lambda_1, \dots, \lambda_n)$  is the intensity vector used to form convex combinations of the observed inputs and outputs. For the convenience of the reader and to improve the clarity of the mathematical formulations, a comprehensive list of the indices, parameters, variables, and abbreviations used throughout the paper is summarized in Appendix B.

Traditional DEA models (such as CCR and BCC) are radial and do not fully account for non-radial slacks in inputs and outputs. To overcome this limitation, the ERM provides a

comprehensive non-radial efficiency score. For a specific unit under evaluation,  $DMU_o$ , the standard ERM model is formulated as:

$$\begin{aligned}
 \min E &= \frac{\frac{1}{m} \sum_{i=1}^m \theta_i}{\frac{1}{s} \sum_{k=1}^s \varphi_k} \\
 \text{s.t. } \sum_{j=1}^n \lambda_j x_{ij} &\leq \theta_i x_{io}, \quad i = 1, \dots, m \\
 \sum_{j=1}^n \lambda_j y_{kj} &\geq \varphi_k y_{ko}, \quad k = 1, \dots, s \\
 \sum_{j=1}^n \lambda_j &= 1 \\
 \lambda_j &\geq 0, \quad j = 1, \dots, n \\
 \theta_i &\leq 1, \quad i = 1, \dots, m \\
 \varphi_k &\geq 1, \quad k = 1, \dots, s
 \end{aligned} \tag{1}$$

In this model,  $\theta_i$  represents the proportional reduction for the  $i$ -th input, and  $\varphi_k$  represents the proportional expansion for the  $k$ -th output.

Let  $(\theta, \varphi, \lambda)$  be the optimal solution of the ERM model for the evaluated  $DMU_o$ . Based on this optimal solution, the virtual targets (projected points) for the inputs and outputs, denoted by  $\widehat{x}_{io}$  and  $\widehat{y}_{ko}$ , are defined as follows:

$$\begin{aligned}
 \widehat{x}_{io} &= \theta_i^* x_{io} = \sum_{j=1}^n \lambda_j^* x_{ij}, \quad i = 1, \dots, m \\
 \widehat{y}_{ko} &= \varphi_k^* y_{ko} = \sum_{j=1}^n \lambda_j^* y_{kj}, \quad k = 1, \dots, s
 \end{aligned} \tag{2}$$

It is crucial to note that these target points belong to the strong efficiency frontier (i.e., they are strongly Pareto-efficient). In standard radial models, the efficiency score merely reflects an equi-proportional reduction in inputs (or expansion in outputs), often projecting the DMU onto the weak efficiency frontier where non-zero residual slacks may still exist. Reaching the strong frontier in such models requires a secondary optimization phase.

In contrast, the ERM is a non-radial approach whose objective function strictly and comprehensively incorporates the contraction ratio ( $\theta_i$ ) for every single input and the expansion ratio ( $\varphi_k$ ) for every single output. Because the model actively minimizes all input ratios and maximizes all output ratios simultaneously, any uncaptured slack would contradict the optimality of the objective value. Consequently, the projected virtual target  $(\widehat{x}_{io}, \widehat{y}_{ko})$  is guaranteed to be a Pareto-efficient operating point. At this point, it is mathematically impossible to further decrease any input without increasing another input or decreasing an output, and similarly impossible to increase any output without decreasing another output or increasing an input.

## 2.2 Centralized resource allocation and target setting mechanism

While conventional DEA models evaluate units independently, Lozano et al. [5] introduced a centralized DEA approach. They argued that when all units (e.g., bank branches) operate under the supervision of a single central decision-maker, evaluating them independently might lead to sub-optimal decisions for the organization as a whole. Instead, the central decision-maker seeks to optimize resource allocation across all units simultaneously to maximize the overall efficiency of the group.

However, traditional centralized models were predominantly radial and focused on either input reduction or output expansion separately. To address this limitation, recent developments in the literature [40] introduced a non-radial centralized model based on the ERM. This model is designed to simultaneously adjust inputs and outputs, provide a unified efficiency score for the entire group, and determine specific targets for each unit.

The fractional mathematical formulation of this centralized ERM model is presented as follows:

$$\begin{aligned}
 \min R &= \frac{\sum_{i=1}^m \theta_i / m}{\sum_{k=1}^s \varphi_k / s} \\
 \text{s. t.} \\
 \sum_{r=1}^n \sum_{j=1}^n \lambda_{jr} x_{ij} &\leq \theta_i \sum_{j=1}^n x_{ij}, \quad i = 1, \dots, m \\
 \sum_{r=1}^n \sum_{j=1}^n \lambda_{jr} y_{kj} &\geq \varphi_k \sum_{j=1}^n y_{kj}, \quad k = 1, \dots, s \\
 \sum_{j=1}^n \lambda_{jr} &= 1, \quad r = 1, \dots, n \\
 \lambda_{jr} &\geq 0, \quad j, r = 1, \dots, n \\
 \theta_i &\leq 1, \quad i = 1, \dots, m \\
 \varphi_k &\geq 1, \quad k = 1, \dots, s
 \end{aligned} \tag{3}$$

To solve this nonlinear fractional programming problem, a standard C-C transformation is applied. By introducing a scalar variable  $\beta > 0$  and defining new variables  $u_i = \beta \theta_i$ ,  $v_k = \beta \varphi_k$ , and  $t_{jr} = \beta \lambda_{jr}$ , the fractional model is transformed into the following equivalent linear programming model:

$$\begin{aligned}
 \min & \frac{\sum_{i=1}^m u_i}{m} \\
 \text{s. t.} \\
 \sum_{r=1}^n \sum_{j=1}^n t_{jr} x_{ij} &\leq u_i \sum_{r=1}^n x_{ir}, \quad i = 1, \dots, m \\
 \sum_{r=1}^n \sum_{j=1}^n t_{jr} y_{kj} &\geq v_k \sum_{r=1}^n y_{kr}, \quad k = 1, \dots, s
 \end{aligned}$$

$$\begin{aligned}
\sum_{j=1}^n t_{jr} &= \beta, \quad r = 1, \dots, n \\
t_{jr} &\geq 0, \quad j, r = 1, \dots, n \\
u_i &\leq \beta, \quad i = 1, \dots, m \\
v_k &\geq \beta, \quad k = 1, \dots, s \\
\sum_{k=1}^s v_k &= s \\
0 &\leq \beta \leq 1
\end{aligned} \tag{4}$$

Once the optimal values  $(\beta^*, u_i^*, v_k^*, t_{jr}^*)$  are obtained from the linear model, the optimal intensity variables are recovered as  $\lambda_{jr}^* = t_{jr}^* / \beta^*$ .

A fundamental property of this centralized approach is its built-in mechanism for target setting and resource reallocation. Let  $x_{ij}$  and  $y_{kj}$  represent the initial resources and outputs of the units before applying the model. Using the optimal intensity variables, the central decision-maker can determine the exact optimal allocation of resources after the evaluation. The new targets (reallocated resources and expected outputs) for each specific unit  $r$  ( $r = 1, \dots, n$ ) are calculated as:

$$\begin{aligned}
\widehat{x}_{ir} &= \sum_{j=1}^n \lambda_{jr}^* x_{ij}, \quad \forall i = 1, \dots, m \\
\widehat{y}_{kr} &= \sum_{j=1}^n \lambda_{jr}^* y_{kj}, \quad \forall k = 1, \dots, s
\end{aligned}$$

As established in previous studies [40], a key characteristic of these newly assigned targets  $(\widehat{x}_{ir}, \widehat{y}_{kr})$  is that they are mathematically guaranteed to be Pareto-efficient (strongly efficient) within the PPS. Furthermore, if we aggregate these individual targets to form an overall target for the entire group  $(\sum_r \widehat{x}_{ir}, \sum_r \widehat{y}_{kr})$ , this aggregated target is also guaranteed to lie on the strong efficient frontier of the group's technology set. This property provides a transparent, step-by-step roadmap for managers to redistribute inputs and outputs optimally among units without any resource wastage.

### 2.3 Fuzzy sets and triangular fuzzy numbers

In real-world applications, particularly in the banking sector, input and output data are often tainted by uncertainty, imprecision, and vagueness. Traditional deterministic models fail to capture this inherent ambiguity. To address this, fuzzy set theory, initially introduced by Zadeh (1965), is employed to model systems under uncertainty.

**Definition 1** Let  $X$  be a universal set. A fuzzy set  $\widetilde{A}$  in  $X$  is characterized by a membership function  $\mu_{\widetilde{A}}(x)$  which associates each element  $x \in X$  with a real number in the interval  $[0, 1]$ . The  $\alpha$ -cut of a fuzzy set  $\widetilde{A}$ , denoted by  $\widetilde{A}_\alpha$ , is a crisp subset of elements whose membership degree is at least  $\alpha$  ( $\alpha \in [0, 1]$ ), defined as:

$$\widetilde{A}_\alpha = \{x \in X \mid \mu_{\widetilde{A}}(x) \geq \alpha\}$$

**Definition 2** A Triangular Fuzzy Number (TFN), denoted by  $\tilde{A} = (a^L, a^M, a^U)$ , is a convex and normal fuzzy set whose membership function  $\mu_{\tilde{A}}(x)$  is defined as piecewise linear:

$$\mu_{\tilde{A}}(x) = \max \left( \min \left( \frac{x - a^L}{a^M - a^L}, \frac{a^U - x}{a^U - a^M} \right), 0 \right)$$

where  $a^L$  and  $a^U$  represent the lower and upper bounds respectively, and  $a^M$  is the most promising (mean) value.

While there are various forms of fuzzy numbers such as interval or trapezoidal fuzzy numbers, TFNs are particularly adopted in this study. Interval numbers merely provide a uniform bound without highlighting the most likely scenario, and trapezoidal numbers assume a flat top (a range of equally most-likely values) which increases computational complexity without necessarily adding value in banking performance evaluation. In contrast, TFNs perfectly align with managerial perspectives by representing the exact pessimistic ( $a^L$ ), most-likely ( $a^M$ ), and optimistic ( $a^U$ ) scenarios. Furthermore, TFNs maintain linearity in membership functions, ensuring computational efficiency and interpretability in large-scale Centralized Resource Allocation models.

**Definition 3** A triangular fuzzy number  $\tilde{A} = (a^L, a^M, a^U)$  is considered non-negative ( $\tilde{A} \geq 0$ ) if and only if  $a^L \geq 0$ . Two TFNs  $\tilde{A}$  and  $\tilde{B} = (b^L, b^M, b^U)$  are considered equal ( $\tilde{A} = \tilde{B}$ ) if  $a^L = b^L$ ,  $a^M = b^M$ , and  $a^U = b^U$ .

**Definition 4:** Let  $\tilde{A} = (a^L, a^M, a^U)$  and  $\tilde{B} = (b^L, b^M, b^U)$  be two non-negative TFNs, and  $k \in \mathbb{R}$  be a crisp scalar. According to Zadeh's extension principle, the basic arithmetic operations are defined as follows:

1) Addition:

$$\tilde{A} \oplus \tilde{B} = (a^L + b^L, a^M + b^M, a^U + b^U)$$

2) Subtraction:

$$\tilde{A} \ominus \tilde{B} = (a^L - b^U, a^M - b^M, a^U - b^L)$$

3) Scalar Multiplication:

$$\begin{aligned} k \otimes \tilde{A} &= (ka^L, ka^M, ka^U), & \text{if } k \geq 0 \\ k \otimes \tilde{A} &= (ka^U, ka^M, ka^L), & \text{if } k < 0 \end{aligned}$$

## 2.4 Developing a fully fuzzy CCR model using a Lexicographic approach for TFNs

In this section, to evaluate the efficiency of DMUs in uncertain environments, a radial DEA model based on the traditional CCR framework is developed in a fully fuzzy context. Assume there are  $n$  DMUs, where each DMU <sub>$j$</sub>  ( $j = 1, \dots, n$ ) uses  $m$  fuzzy inputs  $\tilde{x}_{ij}$  ( $i = 1, \dots, m$ ) to produce  $s$  fuzzy outputs  $\tilde{y}_{rj}$  ( $r = 1, \dots, s$ ).

The input-oriented basic CCR model, when all inputs, outputs, and decision variables (including weight variables  $\tilde{\lambda}$  and the efficiency score  $\tilde{\theta}$ ) are considered fuzzy, is formulated as follows:

$$\min \tilde{\theta}_p$$

$$\begin{aligned}
\text{s.t. } & \sum_{j=1}^n \tilde{\lambda}_j \otimes \tilde{x}_{ij} \leq \tilde{\theta}_p \otimes \tilde{x}_{ip} \quad , \quad i = 1, \dots, m \\
& \sum_{j=1}^n \tilde{\lambda}_j \otimes \tilde{y}_{rj} \geq \tilde{y}_{rp} \quad , \quad r = 1, \dots, s \\
& \tilde{\lambda}_j \geq 0 \quad , \quad j = 1, \dots, n
\end{aligned} \tag{5}$$

In this study, all fuzzy parameters are modeled using TFNs.  $\tilde{A} = (A^L, A^M, A^U)$ . Based on fuzzy arithmetic operations and by expanding the fully fuzzy model using the components of TFNs, the model is decomposed into a set of crisp inequalities. By introducing an index  $k \in \{L, M, U\}$  to represent the three components of the TFNs, and defining the fuzzy efficiency score as  $\tilde{\theta}_p = (\theta_p^L, \theta_p^M, \theta_p^U)$ , the objective function transforms into a Multi-Objective Linear Programming (MOLP) problem aimed at minimizing all three components of the efficiency score simultaneously:

$$\begin{aligned}
& \min (\theta_p^L, \theta_p^M, \theta_p^U) \\
\text{s.t. } & \sum_{j=1}^n \lambda_j^k x_{ij}^k \leq \theta_p^k x_{ip}^k \quad , \quad i = 1, \dots, m \quad , \quad k \in \{L, M, U\} \\
& \sum_{j=1}^n \lambda_j^k y_{rj}^k \geq y_{rp}^k \quad , \quad r = 1, \dots, s \quad , \quad k \in \{L, M, U\} \\
& \theta_p^U \geq \theta_p^M \geq \theta_p^L \geq 0 \\
& \lambda_j^U \geq \lambda_j^M \geq \lambda_j^L \geq 0 \quad , \quad j = 1, \dots, n
\end{aligned} \tag{6}$$

(Note: The last two constraints are included to maintain the standard structural shape of TFNs for the decision variables).

To solve the aforementioned MOLP problem, we employ the lexicographic optimization approach. Hatami-Marbini et al. [28] proposed this method for evaluating efficiency in fuzzy DEA models. Their approach was originally formulated for trapezoidal fuzzy numbers, which necessitates solving four sequential optimization steps. However, since we utilize TFNs in this paper, the structure is adapted accordingly, reducing the optimization process to three sequential steps.

In our lexicographic approach, the minimization of the efficiency score components is performed hierarchically, prioritizing from the upper bound down to the lower bound. The solution steps are detailed as follows:

Step 1: First, the upper bound of the efficiency score is minimized. In this step, the following single-objective model is solved to obtain the optimal value  $\theta_p^U$ :

$$\begin{aligned}
& \min \theta_p^U \\
& \text{s.t. All input, output, and structural constraints mentioned in the MOLP model.}
\end{aligned}$$

Step 2: Next, the middle value of the efficiency score is minimized, provided that the optimal value obtained from the first step ( $\theta_p^U$ ) is preserved:

$$\begin{aligned}
& \min \theta_p^M \\
& \text{s.t. } \theta_p^U = \theta_p^{U*}
\end{aligned}$$

s.t. All input, output, and structural constraints mentioned in the MOLP model.

By solving this model, the optimal value  $\theta_p^M$  is extracted.



Step 3: Finally, the lower bound of the efficiency score is minimized while maintaining the optimal values derived from the previous two steps:

$$\begin{aligned} \min \theta_p^L \\ \text{s.t. } \theta_p^U &= \theta_p^{U*} \\ \theta_p^M &= \theta_p^{M*} \end{aligned}$$

s.t. All input, output, and structural constraints mentioned in the MOLP model.

The optimal value resulting from this final step ( $\theta_p^L$ ), alongside the previously obtained values, provides the unique and final fuzzy efficiency score for the evaluated unit as a precise triangular fuzzy number:  $\widetilde{\theta}_p^* = (\theta_p^{L*}, \theta_p^{M*}, \theta_p^{U*})$ .

### 3 Fully fuzzy centralized resource allocation model

#### 3.1 Model making process

In many real-world applications, DMUs operate under the supervision of a Centralized Decision Maker (CMD) rather than as entirely independent entities. In such environments, the DM seeks to optimize the total resource consumption and production across all DMUs simultaneously. To address the inherent uncertainty in real-world data, we propose a fully fuzzy centralized resource allocation model based on the modified Russell measure.

Consider a system comprising  $n$  DMUs, where each DMU $j$  ( $j = 1, \dots, n$ ) consumes  $m$  inputs to produce  $s$  outputs. Due to data uncertainty, the inputs and outputs are represented as TFNs, denoted by  $\widetilde{x}_{ij} = (x_{ij}^L, x_{ij}^M, x_{ij}^U)$  and  $\widetilde{y}_{kj} = (y_{kj}^L, y_{kj}^M, y_{kj}^U)$ , respectively.

The objective of the centralized DM is to determine a unified efficiency score by simultaneously contracting inputs and expanding outputs across the entire system. Accordingly, the decision variables are defined as follows:

$\widetilde{\theta}_i$ : The fuzzy contraction ratio for the  $i$ -th input across all DMUs.

$\widetilde{\varphi}_k$ : The fuzzy expansion ratio for the  $k$ -th output across all DMUs.

$\widetilde{\lambda}_{jr}$ : The fuzzy reallocation weight representing the contribution of DMU $r$  in evaluating DMU $j$ .

Based on these assumptions, the fully fuzzy fractional centralized model is formulated as follows:

$$\begin{aligned} \min \widetilde{R} &= \frac{\sum_{i=1}^m \widetilde{\theta}_i / m}{\sum_{k=1}^s \widetilde{\varphi}_k / s} \\ \text{s.t. } \sum_{r=1}^n \sum_{j=1}^n \widetilde{\lambda}_{jr} \otimes \widetilde{x}_{ij} &\leq \widetilde{\theta}_i \otimes \sum_{j=1}^n \widetilde{x}_{ij} \quad , \quad i = 1, \dots, m \\ \sum_{r=1}^n \sum_{j=1}^n \widetilde{\lambda}_{jr} \otimes \widetilde{y}_{kj} &\geq \widetilde{\varphi}_k \otimes \sum_{j=1}^n \widetilde{y}_{kj} \quad , \quad k = 1, \dots, s \\ \sum_{j=1}^n \widetilde{\lambda}_{jr} &= \widetilde{1} \quad , \quad r = 1, \dots, n \\ \widetilde{\lambda}_{jr} &\geq 0 \quad , \quad j, r = 1, \dots, n \\ \widetilde{\theta}_i &\leq 1 \quad , \quad i = 1, \dots, m \\ \widetilde{\varphi}_k &\geq 1 \quad , \quad k = 1, \dots, s \end{aligned} \tag{7}$$

(7)

The objective function  $\tilde{R}$  evaluates the overall fuzzy efficiency of the system by minimizing the ratio of average input contraction to average output expansion.

The first set of constraints guarantees that the total redistributed fuzzy inputs do not exceed the contracted total available inputs in the system. Similarly, the second set of constraints ensures that the total redistributed fuzzy outputs are at least equal to the expanded total current outputs. The third and fourth constraints represent the standard convexity and non-negativity conditions for the redistribution weights. Finally, the bounding constraints ( $\tilde{\theta}_1 \leq 1$  and  $\tilde{\varphi}_k \geq 1$ ) ensure that inputs are only reduced and outputs are only increased.

By utilizing the arithmetic operations of TFNs and introducing the index  $h \in \{L, M, U\}$  to represent the lower, middle, and upper bounds of the fuzzy sets, the fully fuzzy model can be decomposed. Based on the rules of fuzzy division, the upper bound of the objective function is obtained by dividing the upper bound of the numerator by the lower bound of the denominator (and vice versa for the lower bound). Thus, the model transforms into an MOFP problem:

$$\begin{aligned} \min \left( R^L = \frac{\sum_{i=1}^m \theta_i^L / m}{\sum_{k=1}^s \varphi_k^U / s}, \quad R^M = \frac{\sum_{i=1}^m \theta_i^M / m}{\sum_{k=1}^s \varphi_k^M / s}, \quad R^U = \frac{\sum_{i=1}^m \theta_i^U / m}{\sum_{k=1}^s \varphi_k^L / s} \right) \\ \text{s.t.} \quad \sum_{r=1}^n \sum_{j=1}^n \lambda_{jr}^h x_{ij}^h \leq \theta_i^h \sum_{j=1}^n x_{ij}^h, \quad i = 1, \dots, m, \quad h \in \{L, M, U\} \\ \sum_{r=1}^n \sum_{j=1}^n \lambda_{jr}^h y_{kj}^h \geq \varphi_k^h \sum_{j=1}^n y_{kj}^h, \quad k = 1, \dots, s, \quad h \in \{L, M, U\} \\ \sum_{j=1}^n \lambda_{jr}^h = 1 \\ \lambda_{jr}^U \geq \lambda_{jr}^M \geq \lambda_{jr}^L \geq 0, \quad j, r = 1, \dots, n \\ 1 \geq \theta_i^U \geq \theta_i^M \geq \theta_i^L \geq 0, \quad i = 1, \dots, m \\ \varphi_k^U \geq \varphi_k^M \geq \varphi_k^L \geq 1, \quad k = 1, \dots, s \end{aligned} \quad (7)$$

To optimize the derived MOFP model, we employ the three-step lexicographic method. This approach hierarchically minimizes the fuzzy components from the most pessimistic (upper bound) to the most optimistic (lower bound) perspective:

Step 1: Minimize the upper bound of the efficiency score:

$$\min R^U = \frac{\sum_{i=1}^m \theta_i^U / m}{\sum_{k=1}^s \varphi_k^L / s}$$

s.t. All decomposed structural and bounding constraints for  $h \in \{L, M, U\}$

Let the optimal objective value be  $R^U$ .

Step 2: Minimize the middle component, preserving the optimal upper bound obtained in Step 1:

$$\begin{aligned} \min R^M = \frac{\sum_{i=1}^m \theta_i^M / m}{\sum_{k=1}^s \varphi_k^M / s} \\ \text{s.t.} \quad \frac{\sum_{i=1}^m \theta_i^U / m}{\sum_{k=1}^s \varphi_k^L / s} = R^U \end{aligned}$$

s.t. All decomposed structural and bounding constraints for  $h \in \{L, M, U\}$

Let the optimal objective value be  $R^M$ .

Step 3: Minimize the lower bound, preserving the optimal values from both Step 1 and Step 2:

$$\begin{aligned} \min R^L &= \frac{\sum_{i=1}^m \theta_i^L / m}{\sum_{k=1}^s \varphi_k^U / s} \\ \text{s.t. } &\frac{\sum_{i=1}^m \theta_i^U / m}{\sum_{k=1}^s \varphi_k^L / s} = R^{U*} \\ &\frac{\sum_{i=1}^m \theta_i^M / m}{\sum_{k=1}^s \varphi_k^M / s} = R^{M*} \end{aligned}$$

s.t. All decomposed structural and bounding constraints for  $h \in \{L, M, U\}$

Let the optimal objective value be  $R^L$ . The final exact triangular fuzzy efficiency score is represented as  $\widetilde{R} = (R^L, R^M, R^U)$ .

### 3.2 Linearized Lexicographic optimization procedure

By applying the C-C transformation, we convert the nonlinear MOFP model into a sequence of linear programming (LP) models. We introduce a positive scalar variable  $t$  and define new variables  $T_i^h = t\theta_i$ ,  $\Phi_k^h = t\varphi_k$ , and  $\Lambda_{jr}^h = t\lambda_{jr}$ . The three-step linear lexicographic procedure is formulated as follows:

Step 1: Minimizing the Upper Bound ( $R^U$ )

In the first step, we linearize the upper bound by setting the denominator of  $R^U$  equal to 1 using the variable  $t^U$ .

$$\begin{aligned} \min & \sum_{i=1}^m T_i^U / m \\ \text{s.t. } & \sum_{k=1}^s \Phi_k^L / s = 1 \\ & \sum_{r=1}^n \sum_{j=1}^n \Lambda_{jr}^h x_{ij}^h \leq T_i^h \sum_{j=1}^n x_{ij}^h, \quad i = 1, \dots, m, \quad h \in \{L, M, U\} \\ & \sum_{r=1}^n \sum_{j=1}^n \Lambda_{jr}^h y_{kj}^h \geq \Phi_k^h \sum_{j=1}^n y_{kj}^h, \quad k = 1, \dots, s, \quad h \in \{L, M, U\} \\ & \sum_{j=1}^n \Lambda_{jr}^h = t^U \\ & \Lambda_{jr}^U \geq \Lambda_{jr}^M \geq \Lambda_{jr}^L \geq 0, \quad j, r = 1, \dots, n \\ & t^U \geq T_i^U \geq T_i^M \geq T_i^L \geq 0, \quad i = 1, \dots, m \\ & \Phi_k^U \geq \Phi_k^M \geq \Phi_k^L \geq t^U, \quad k = 1, \dots, s \\ & t^U > 0 \end{aligned}$$

(8)

Let the optimal objective value of this step be  $R^{U*}$ .

Step 2: Minimizing the Middle Component ( $R^M$ )

Here, we set the denominator of  $R^M$  equal to 1 using a new scalar  $t^M$ . The optimal value from Step 1 is incorporated as a linear constraint.

$$\begin{aligned}
& \min \sum_{i=1}^m T_i^M / m \\
& \text{s.t.} \quad \sum_{k=1}^s \Phi_k^M / s = 1 \\
& \quad \sum_{i=1}^m T_i^U / m = R^{U*} \left( \sum_{k=1}^s \Phi_k^L / s \right) \\
& \quad \sum_{r=1}^n \sum_{j=1}^n \Lambda_{jr}^h x_{ij}^h \leq T_i^h \sum_{j=1}^n x_{ij}^h, \quad i = 1, \dots, m, \quad h \in \{L, M, U\} \\
& \quad \sum_{r=1}^n \sum_{j=1}^n \Lambda_{jr}^h y_{kj}^h \geq \Phi_k^h \sum_{j=1}^n y_{kj}^h, \quad k = 1, \dots, s, \quad h \in \{L, M, U\} \\
& \quad \sum_{j=1}^n \Lambda_{jr}^h = t^M \\
& \quad \Lambda_{jr}^U \geq \Lambda_{jr}^M \geq \Lambda_{jr}^L \geq 0, \quad j, r = 1, \dots, n \\
& \quad t^M \geq T_i^U \geq T_i^M \geq T_i^L \geq 0, \quad i = 1, \dots, m \\
& \quad \Phi_k^U \geq \Phi_k^M \geq \Phi_k^L \geq t^M, \quad k = 1, \dots, s \\
& \quad t^M > 0
\end{aligned} \tag{9}$$

Let the optimal objective value of this step be  $R^{M*}$ .

Step 3: Minimizing the Lower Bound ( $R^L$ )

Finally, we set the denominator of  $R^L$  equal to 1 using  $t^L$ , preserving the optimal values from both previous steps as linear constraints.

$$\begin{aligned}
& \min \sum_{i=1}^m T_i^L / m \\
& \text{s.t.} \quad \sum_{k=1}^s \Phi_k^U / s = 1 \\
& \quad \sum_{i=1}^m T_i^U / m = R^{U*} \left( \sum_{k=1}^s \Phi_k^L / s \right) \\
& \quad \sum_{i=1}^m T_i^M / m = R^{M*} \left( \sum_{k=1}^s \Phi_k^M / s \right) \\
& \quad \sum_{r=1}^n \sum_{j=1}^n \Lambda_{jr}^h x_{ij}^h \leq T_i^h \sum_{j=1}^n x_{ij}^h, \quad i = 1, \dots, m, \quad h \in \{L, M, U\} \\
& \quad \sum_{r=1}^n \sum_{j=1}^n \Lambda_{jr}^h y_{kj}^h \geq \Phi_k^h \sum_{j=1}^n y_{kj}^h, \quad k = 1, \dots, s, \quad h \in \{L, M, U\} \\
& \quad \sum_{j=1}^n \Lambda_{jr}^h = t^L \\
& \quad \Lambda_{jr}^U \geq \Lambda_{jr}^M \geq \Lambda_{jr}^L \geq 0, \quad j, r = 1, \dots, n
\end{aligned}$$

$$\begin{aligned}
t^L \geq T_i^U \geq T_i^M \geq T_i^L \geq 0 \quad , \quad i = 1, \dots, m \\
\Phi_k^U \geq \Phi_k^M \geq \Phi_k^L \geq t^L \quad , \quad k = 1, \dots, s \\
t^L > 0
\end{aligned} \tag{10}$$

After solving Step 3, the final exact triangular fuzzy efficiency score  $\widetilde{R}^* = (R^{L*}, R^{M*}, R^{U*})$  is determined.

### 3.3 Key characteristics and computational considerations of the linearized model

The proposed linearized lexicographic procedure possesses several vital mathematical and computational characteristics that warrant detailed explanation. Firstly, the elimination of the convexity constraint (originally  $\sum_{j=1}^n \lambda_{jr}^h = 1$ , which translates to  $\sum_{j=1}^n \Lambda_{jr}^h = t^h$  after the C-C transformation) indicates that the centralized system can be evaluated under the assumption of Constant Returns to Scale (CRS). Secondly, the bounding restrictions on the original contraction and expansion ratios ( $\theta_i^h \leq 1$  and  $\varphi_k^h \geq 1$ ) are seamlessly mapped into linear boundaries  $T_i^h \leq t^h$  and  $\Phi_k^h \geq t^h$ , ensuring that inputs are strictly contracted and outputs are strictly expanded. Furthermore, in the second and third steps of the lexicographic process, the optimal efficiency values obtained from preceding steps ( $R^U$  and  $R^M$ ) are preserved using strictly linear constraints. This is achieved by equating the numerator to the product of the optimal ratio and the denominator (e.g.,  $\sum_{i=1}^m T_i^U / m = R^U \sum_{k=1}^s \Phi_k^L / s$ ). This strategic algebraic manipulation guarantees that the feasible region remains strictly linear, entirely avoiding the complexities of nonlinear equality constraints.

A fundamental requirement of the C-C transformation is the strict positivity of the scalar variable ( $t^h > 0$ ). This condition is imperative to ensure that the original fractional denominator is non-zero and that the transformation remains mathematically reversible. However, standard linear programming (LP) solvers rely on closed feasible regions and cannot inherently process strict inequalities. To mathematically resolve this limitation, a non-Archimedean infinitesimal value, denoted by  $\epsilon$ , is introduced, modifying the strict positivity constraint to  $t^h \geq \epsilon$ . In practical computational implementations—using algebraic modeling languages such as GAMS or LINGO—this non-Archimedean  $\epsilon$  is replaced by a sufficiently small positive constant (e.g.,  $10^{-6}$ ). This practical adjustment satisfies the positivity condition, maintains model feasibility, and averts numerical instability during the optimization process.

Successfully solving this sequence of LP models not only yields the exact overall fuzzy efficiency score  $\widetilde{R}^* = (R^L, R^M, R^U)$  but also provides the optimal values for all transformed decision variables ( $T_i^h, \Phi_k^h, \Lambda_{jr}^h$ , and  $t^h$ ). By applying the inverse C-C transformation ( $\theta_i^h = T_i^h / t^h$ ,  $\varphi_k^h = \Phi_k^h / t^h$ , and  $\lambda_{jr}^h = \Lambda_{jr}^h / t^h$ ), the Centralized Decision Maker can retrieve the exact optimal input contractions and output expansions. As will be discussed in the subsequent section, these optimal parameters serve as the mathematical foundation for establishing precise performance targets and designing an optimal resource reallocation scheme across all DMUs within the system.

### 3.4 Optimal resource allocation and target setting

Once the three-step linearized lexicographic procedure is optimally solved, the CDM obtains the optimal values for all transformed variables ( $T_i^h, \Phi_k^h, \Lambda_{jr}^h$ , and  $t^h$  for  $h \in \{L, M, U\}$ ). The first

step in establishing an optimal resource allocation plan is to retrieve the original pre-transformation variables using the inverse Charnes-Cooper substitutions:

$$\theta_i^{h*} = \frac{T_i^{h*}}{t^{h*}}, \quad \varphi_k^{h*} = \frac{\Phi_k^{h*}}{t^{h*}}, \quad \lambda_{jr}^{h*} = \frac{\Lambda_{jr}^{h*}}{t^{h*}}, \quad h \in \{L, M, U\}$$

With these optimal parameters extracted, the CDM can determine the optimally allocated targets from two interconnected perspectives: the macro-level systemic targets based on  $\theta$  and  $\varphi$ , and the micro-level DMU-specific allocations based on  $\lambda$ .

### 1. Systemic Resource Allocation and Target Setting (Based on $\theta^*$ and $\varphi^*$ ):

The variables  $\theta_i^h$  and  $\varphi_k^h$  represent the optimal contraction of total input resources and the optimal expansion of total output productions across the entire centralized system, respectively. Therefore, the overall optimal fuzzy target levels for the total consumption of resource  $i$  and the total generation of output  $k$  are defined as:

$$\begin{aligned} \widetilde{X}_i^{\text{Total}*} &= \left( \theta_i^{L*} \sum_{j=1}^n x_{ij}^L, \theta_i^{M*} \sum_{j=1}^n x_{ij}^M, \theta_i^{U*} \sum_{j=1}^n x_{ij}^U \right), \quad i = 1, \dots, m \\ \widetilde{Y}_k^{\text{Total}*} &= \left( \varphi_k^{L*} \sum_{j=1}^n y_{kj}^L, \varphi_k^{M*} \sum_{j=1}^n y_{kj}^M, \varphi_k^{U*} \sum_{j=1}^n y_{kj}^U \right), \quad k = 1, \dots, s \end{aligned} \quad (11)$$

These equations indicate the total resource budget and the overall production goals that the centralized system should aim for to achieve maximum fuzzy efficiency.

### 2. DMU-Specific Resource Allocation (Based on $\lambda^*$ ):

While the systemic targets provide the overall budget, the intensity variables ( $\lambda_{jr}^{h*}$ ) dictate exactly how these resources should be reallocated among individual DMUs to project them onto the efficient frontier. The optimal fuzzy input allocation for a specific DMU $r$ , denoted by  $\widehat{x}_{ir}^*$ , and its corresponding optimal fuzzy output target, denoted by  $\widehat{y}_{kr}^*$ , are formulated as:

$$\begin{aligned} \widehat{x}_{ir}^{h*} &= \sum_{j=1}^n \lambda_{jr}^{h*} x_{ij}^h, \quad h \in \{L, M, U\}, i = 1, \dots, m, k = 1, \dots, n \\ \widehat{y}_{kr}^{h*} &= \sum_{j=1}^n \lambda_{jr}^{h*} y_{kj}^h, \quad h \in \{L, M, U\}, r = 1, \dots, s, k = 1, \dots, n \end{aligned} \quad (12)$$

### 3. Integration of Allocations:

According to the structural constraints of the proposed centralized model, the sum of the individually allocated resources (via  $\lambda$ ) strictly bounds the systemic targets (via  $\theta$  and  $\varphi$ ). Mathematically, for any uncertainty level  $h \in \{L, M, U\}$ :

$$\begin{aligned} \sum_{r=1}^n \widehat{x}_{ir}^{h*} &\leq \theta_i^{h*} \sum_{j=1}^n x_{ij}^h \\ \sum_{r=1}^n \widehat{y}_{kr}^{h*} &\geq \varphi_k^{h*} \sum_{j=1}^n y_{kj}^h \end{aligned}$$

To ensure that the proposed allocations are practically implementable and perfectly efficient, it is crucial to demonstrate that the sum of individual allocations mathematically matches the systemic targets without any residual slacks. This characteristic is rigorously proven in Theorem 1.

**Theorem 1 (Binding Constraints at Optimality).**

In the optimal solution of the proposed non-radial centralized resource allocation model, all resource and production constraints strictly hold as equalities. Consequently, the total allocated inputs and generated outputs across all DMUs perfectly match the optimal systemic targets.

**Proof:**

We prove this theorem by contradiction. Let  $(\theta^h, \varphi^h, \lambda^h)$  be the optimal solution for the centralized model at a given uncertainty level  $h \in \{L, M, U\}$ .

First, consider the input constraints. Suppose that for at least one specific input resource  $i_0$ , the constraint holds as a strict inequality at optimality:

$$\sum_{r=1}^n \sum_{j=1}^n \lambda_{jr}^h x_{i_0j}^h < \theta_{i_0}^h \sum_{j=1}^n x_{i_0j}^h$$

Since inputs are strictly positive ( $x_{ij} > 0$ ), we can define a new contraction parameter  $\widehat{\theta}_{i_0}^h$  such that:

$$\widehat{\theta}_{i_0}^h = \frac{\sum_{r=1}^n \sum_{j=1}^n \lambda_{jr}^h x_{i_0j}^h}{\sum_{j=1}^n x_{i_0j}^h} < \theta_{i_0}^h$$

By replacing  $\theta_{i_0}^h$  with  $\widehat{\theta}_{i_0}^h$ , the feasible region is not violated. However, since the objective function of the fractional model (or its linearized lexicographic steps) strictly minimizes the average of  $\theta_i^h$  in the numerator, substituting  $\theta_{i_0}^h$  with a strictly smaller value  $\widehat{\theta}_{i_0}^h$  yields a strictly better (lower) objective function value. This contradicts the assumption that  $\theta_{i_0}^h$  was the optimal solution. Thus, the input constraints must hold as equalities.

Second, consider the output constraints. Suppose that for at least one specific output  $k_0$ , the inequality is strict:

$$\sum_{r=1}^n \sum_{j=1}^n \lambda_{jr}^h y_{k_0j}^h > \varphi_{k_0}^h \sum_{j=1}^n y_{k_0j}^h$$

Similarly, we can define a new expansion parameter  $\widehat{\varphi}_{k_0}^h$ :

$$\widehat{\varphi}_{k_0}^h = \frac{\sum_{r=1}^n \sum_{j=1}^n \lambda_{jr}^h y_{k_0j}^h}{\sum_{j=1}^n y_{k_0j}^h} > \varphi_{k_0}^h$$

Since the objective function aims to maximize the expansion variables  $\varphi_k^h$  (which act as the denominator in the original fractional model or the bounding constraints in the linearized form), increasing  $\varphi_{k_0}^h$  to  $\widehat{\varphi}_{k_0}^h$  strictly improves the overall efficiency score without violating any constraints. This again contradicts the optimality of  $\varphi_{k_0}^h$ . Therefore, at the optimal solution, both input and output inequalities must strictly bind as equalities:

$$\sum_{r=1}^n \widehat{x}_{ir}^h = \theta_i^h \sum_{j=1}^n x_{ij}^h \quad \text{and} \quad \sum_{r=1}^n \widehat{y}_{kr}^h = \varphi_k^h \sum_{j=1}^n y_{kj}^h$$

**4. Managerial Implications:**

Theorem 1 provides significant managerial insights for the CDM. In standard DEA models, the presence of slacks often implies that resources are wasted or targets are loosely set, which complicates the implementation of restructuring plans. However, the proposed non-radial centralized model mathematically guarantees a slack-free resource allocation scheme.

From a practical perspective, this means:

1. Zero Resource Waste: Every unit of input budget determined by the systemic contraction targets ( $\widetilde{X}_i^{\text{Total}}$ ) is precisely and completely distributed among the operating DMUs. No resources are left unallocated or squandered.
2. Exact Production Matching: The sum of the production goals assigned to individual branches ( $\widetilde{Y}_k^{\text{Total}}$ ) perfectly fulfills the overarching production targets expected by the headquarters.
3. Fairness and Feasibility: Since the macro-level budgets and micro-level quotas are mathematically synchronized, the CDM can confidently enforce these targets, knowing the proposed plan is globally feasible and logically projects the entire organizational network onto the fully fuzzy efficient frontier.

### 3.5 Executive algorithm for the proposed methodology

To synthesize the mathematical formulations developed in the previous sections into a clear, computable procedure, we present the following step-by-step algorithm. This algorithmic framework guides the CDM from raw fuzzy data collection to the final optimal allocation of resources and targets.

#### Algorithm: The Lexicographic centralized resource allocation procedure under fuzzy environment

##### Step 1: Initialization and Data Collection

- Identify the set of  $n$  DMUs operating under a centralized control system.
- Collect the input and output data as TFNs:  $\widetilde{x}_{ij} = (x_{ij}^L, x_{ij}^M, x_{ij}^U)$  for  $m$  inputs, and  $\widetilde{y}_{kj} = (y_{kj}^L, y_{kj}^M, y_{kj}^U)$  for  $s$  outputs.
- Define a sufficiently small strictly positive constant  $\epsilon$  (e.g.,  $10^{-6}$ ) to facilitate the C-C transformation.

##### Step 2: Phase I Optimization (Upper Bound Minimization)

- Construct the linearized centralized model (8) for the upper uncertainty level ( $h = U$ ). In accordance with the lexicographic minimization logic for fuzzy numbers, the upper bound is minimized first to aggressively push the fuzzy set towards efficiency.
- Solve the linear programming problem to minimize the aggregated upper-bound input contractions.
- Output: Obtain the optimal objective function value  $Z^{U*}$ , and the corresponding optimal transformed variables  $T_i^{U*}$ ,  $\Phi_k^{U*}$ ,  $\Lambda_{jr}^{U*}$ , and  $t^{U*}$ .

##### Step 3: Phase II Optimization (Middle Bound Minimization)

- Construct the linearized centralized model (9) for the middle uncertainty level ( $h = M$ ).
- Incorporate the optimal objective value from the previous step ( $Z^U$ ) as an exact equality constraint to preserve the structural integrity and the lexicographic priority of the fuzzy number.
- Solve the linear programming problem.
- Output: Obtain the optimal objective function value  $Z^M$ , and the optimal transformed variables  $T_i^M$ ,  $\Phi_k^M$ ,  $\Lambda_{jr}^M$ , and  $t^M$ .



**Step 4: Phase III Optimization (Lower Bound Minimization)**

- Construct the linearized centralized model (10) for the lower uncertainty level ( $h = L$ ).
- Incorporate both  $Z^U$  and  $Z^M$  as exact equality constraints.
- Solve the final linear programming problem.
- Output: Obtain the optimal transformed variables  $T_i^{L*}$ ,  $\Phi_k^{L*}$ ,  $\Lambda_{jr}^{L*}$ , and  $t^{L*}$ .

**Step 5: Inverse Transformation and Parameter Extraction**

- For all uncertainty levels  $h \in \{U, M, L\}$ , apply the inverse C-C transformation to retrieve the original optimal parameters:
  - Optimal systemic contractions:  $\theta_i^h = T_i^h/t^h$
  - Optimal systemic expansions:  $\varphi_k^h = \Phi_k^h/t^h$
  - Optimal allocation intensities:  $\lambda_{jr}^h = \Lambda_{jr}^h/t^h$

**Step 6: Systemic Macro-Target Setting**

- Utilize the extracted  $\theta_i^h$  and  $\varphi_k^h$  to calculate the overall optimal fuzzy targets for the entire system by (11):
  - Total Systemic Input Budget:  $\widetilde{X}_i^{\text{Total}}$
  - Total Systemic Output Goal:  $\widetilde{Y}_k^{\text{Total}}$

**Step 7: Micro-Level Resource Allocation**

- Utilize the optimal intensity variables  $\lambda_{jr}^h$  to compute the exact, DMU-specific resource allocations ( $\widetilde{x}_{ir}$ ) and production targets ( $\widetilde{y}_{kr}$ ) for each individual branch  $r$  (Considering (12)). Implement the resulting optimal blueprint across the organizational network.

**4 Application in bank branches**

To quantitatively assess the applicability and efficiency of the proposed mathematical framework, the model is deployed on a real-world network of fourteen Refah Kargaran Bank branches. The banking sector, characterized by shared operational goals and a centralized management structure, serves as an ideal environment for Centralized DEA (CDEA).

**4.1 Case description and data set**

Our analytical scope hinges on six crucial performance metrics—comprising three inputs ( $I_1, I_2, I_3$ ) and three outputs ( $O_1, O_2, O_3$ )—carefully selected to reflect the operational and financial dimensions of the branches. The inputs defining the operational context include the workforce size ( $I_1$ ), the physical scale or space of each facility ( $I_2$ ), and the average client demand ( $I_3$ ). On the production side, the outputs used for evaluation consist of average institutional resources ( $O_1$ ), average operational expenses ( $O_2$ ), and the rate of activity/service provision ( $O_3$ ).

Given the inherent uncertainties in the banking environment—such as fluctuating client demands, varying daily transaction volumes, and imprecise estimations of physical capacities—the data cannot be accurately captured as crisp values. Consequently, all input and output parameters are modeled as TFNs, denoted by  $(L, M, U)$ . The empirical data set encompassing

the fuzzy inputs and outputs for all fourteen DMUs is consolidated in Table 1 and Table 2, respectively.

**Table 1** Fuzzy input data

| DMU   | I1 L | I1 M | I1 U | I2 L | I2 M | I2 U | I3 L  | I3 M  | I3 U  |
|-------|------|------|------|------|------|------|-------|-------|-------|
| DMU1  | 4    | 8    | 14   | 121  | 135  | 216  | 1246  | 3115  | 5295  |
| DMU2  | 7    | 11   | 15   | 428  | 535  | 963  | 10424 | 20848 | 35441 |
| DMU3  | 11   | 13   | 20   | 433  | 542  | 758  | 2440  | 6102  | 8542  |
| DMU4  | 4    | 8    | 15   | 206  | 295  | 472  | 2970  | 4244  | 6366  |
| DMU5  | 5    | 7    | 9    | 156  | 392  | 548  | 1234  | 2469  | 3950  |
| DMU6  | 7    | 13   | 19   | 501  | 627  | 877  | 4936  | 12341 | 22213 |
| DMU7  | 3    | 5    | 7    | 74   | 124  | 173  | 9636  | 13766 | 19272 |
| DMU8  | 4    | 6    | 11   | 96   | 240  | 408  | 2357  | 4715  | 8015  |
| DMU9  | 6    | 7    | 13   | 288  | 320  | 448  | 7142  | 14284 | 21426 |
| DMU10 | 2    | 4    | 7    | 132  | 165  | 231  | 1501  | 3753  | 5254  |
| DMU11 | 3    | 5    | 9    | 279  | 466  | 838  | 2401  | 4802  | 9123  |
| DMU12 | 4    | 6    | 9    | 496  | 552  | 772  | 1606  | 4015  | 6424  |
| DMU13 | 4    | 7    | 12   | 246  | 274  | 520  | 584   | 731   | 1388  |
| DMU14 | 4    | 6    | 10   | 164  | 411  | 657  | 4889  | 6112  | 9168  |

**Table 2** Fuzzy output data

| DMU   | O1 L  | O1 M   | O1 U   | O2 L   | O2 M   | O2 U   | O3 L | O3 M  | O3 U  |
|-------|-------|--------|--------|--------|--------|--------|------|-------|-------|
| DMU1  | 16682 | 41705  | 79239  | 112986 | 161409 | 274395 | 565  | 1131  | 1583  |
| DMU2  | 42380 | 47089  | 65924  | 315679 | 450970 | 631358 | 5053 | 10107 | 14149 |
| DMU3  | 49975 | 62469  | 118691 | 152073 | 380183 | 608292 | 2203 | 3673  | 6244  |
| DMU4  | 34477 | 38308  | 57462  | 99933  | 249834 | 374751 | 1684 | 2406  | 4330  |
| DMU5  | 17529 | 25042  | 37563  | 140929 | 176162 | 264243 | 1338 | 2231  | 3123  |
| DMU6  | 92645 | 102939 | 154408 | 285274 | 356593 | 534889 | 5584 | 11169 | 17870 |
| DMU7  | 21367 | 23742  | 45109  | 99253  | 165422 | 281217 | 2384 | 3406  | 6130  |
| DMU8  | 30279 | 37849  | 56773  | 154097 | 192622 | 327457 | 2645 | 3779  | 7180  |
| DMU9  | 22412 | 44825  | 71720  | 151056 | 251760 | 453168 | 542  | 1357  | 1899  |
| DMU10 | 16070 | 17856  | 30355  | 90837  | 100930 | 151395 | 543  | 1359  | 2174  |
| DMU11 | 12955 | 25911  | 41457  | 150116 | 166796 | 300232 | 2001 | 2859  | 4288  |
| DMU12 | 24321 | 30402  | 42562  | 157179 | 174644 | 261966 | 2116 | 3024  | 5745  |
| DMU13 | 21180 | 42361  | 76249  | 225430 | 250478 | 425812 | 0    | 0     | 0     |
| DMU14 | 13152 | 26304  | 44716  | 172988 | 216235 | 410846 | 1979 | 2828  | 4807  |

## 4.2 Computational procedure and reproducibility

The proposed three-step lexicographic FFCDEA model requires a robust algorithmic execution, particularly due to the sequential dependency of the optimization phases ( $U \rightarrow M \rightarrow L$ ). The mathematical formulations were transcribed into computational algorithms and solved using the Python programming language, leveraging the 'PuLP' algebraic modeling library for linear programming.

To ensure full transparency, reproducibility, and to facilitate future adaptations by the scientific community, the complete source code, along with a concise execution manual, is made publicly available. Researchers can access these computational assets as Supplementary Material attached to this paper.

The execution of the lexicographic model yields a highly multidimensional dataset. For each of the 14 branches, the model generates optimal centralized targets  $(\hat{X}, \hat{Y})$ , structural

adjustment factors ( $\theta$ ,  $\varphi$ ), and dual variables ( $\lambda$ ) across three distinct fuzzy boundaries (Lower, Middle, Upper). Integrating this voluminous data directly into the main text would obscure the core analytical narrative. Therefore, a structured presentation strategy is adopted:

1. Macro-Level Analysis (Section 4.3): The systemic performance, representing the bank as a unified entity, is analyzed in the main text.
2. Micro-Level Highlights (Section 4.4): Key managerial insights and aggregated targets for selected branches (e.g., at the Middle bound M) are discussed to demonstrate intra-organizational resource reallocation.
3. Comprehensive Output (Appendix B): The exhaustive, finely granulated tables detailing all optimal values for every DMU across all variables and bounds are strategically placed in the Supplementary Appendices. This ensures the methodological rigor is fully documented without compromising the manuscript's readability.

### 4.3 Systemic performance evaluation

In the first phase of our analysis, the performance of the bank is evaluated from a macro perspective, treating the network of 14 branches as a single unified entity. The Centralized DEA model aims to optimize the total consumption of inputs and generation of outputs across the entire network. Table 3 presents the aggregate initial values alongside the optimal systemic targets computed at the most probable fuzzy bound (Middle bound, M).

**Table 3** Systemic Initial Values vs. Optimal Targets (Middle Bound - M)

| Variable | Description     | Initial Total System | Optimal Target System | Adjustment Factor ( $\theta^*$ , $\varphi^*$ ) | Required Change (%) |
|----------|-----------------|----------------------|-----------------------|------------------------------------------------|---------------------|
| $I_1$    | Workforce       | 106.00               | 106.00                | $\theta_{I1}^* = 1.000$                        | 0.00%               |
| $I_2$    | Physical Space  | 5078.00              | 4379.67               | $\theta_{I2}^* = 0.862$                        | -13.8%              |
| $I_3$    | Client Demand   | 101297.00            | 101297.00             | $\theta_{I3}^* = 1.000$                        | 0.00%               |
| $O_1$    | Inst. Resources | 566802.00            | 689126.72             | $\varphi_{O1}^* = 1.216$                       | +21.6%              |
| $O_2$    | Oper. Expenses  | 3294038.00           | 3294038.00            | $\varphi_{O2}^* = 1.000$                       | 0.00%               |
| $O_3$    | Activity Rate   | 49329.00             | 61039.66              | $\varphi_{O3}^* = 1.237$                       | +23.7%              |

Note: The overall systemic fuzzy efficiency at the Middle bound is  $R_M^* = 0.8289$ .

As depicted in Table 3, the overall systemic efficiency score at the middle bound ( $R_M$ ) stands at approximately 0.8289, indicating that the banking network operates at roughly 82.9% of its maximum potential efficiency. To project the system onto the technically efficient frontier, significant structural adjustments are prescribed. While the total workforce ( $I_1$ ) and client demand ( $I_3$ ) remain perfectly scaled ( $\theta = 1.00$ ), the system exhibits an excess in physical space ( $I_2$ ), requiring a contraction of approximately 13.8% across the network.

Concurrently, on the output side, the centralized model dictates a substantial expansion. To justify the current level of inputs, the total institutional resources ( $O_1$ ) and the activity rate ( $O_3$ ) must be augmented by 21.6% and 23.7%, respectively. These systemic targets provide a strategic roadmap for top-level management to align the bank's total physical footprint with its production capabilities.

### 4.4 DMU-level target setting and resource allocation (Middle bound analysis)

While systemic targets define the macro-level strategic goals, the true utility of the Centralized DEA framework lies in its ability to dictate micro-level operational reallocations. Unlike standard DEA models that independently project underperforming DMUs onto the efficiency

frontier (often ignoring the system's total resource capacity), the FFCDEA model dynamically reallocates total available resources among all 14 branches. This global optimization ensures that the system collectively achieves the systemic targets discussed in Section 4.3.

This centralized mechanism implies a compensatory relationship among the branches: while the network as a whole might contract an input (e.g., Physical Space,  $I_2$ ), specific high-performing branches might simultaneously experience an expansion in that same input to absorb operations from downsizing peers.

To thoroughly examine this reallocation strategy, Table 4 presents the complete set of initial values and their corresponding optimal targets at the most probable fuzzy bound (Middle bound, M) for all 14 DMUs across the six inputs and outputs. (Note: Results for the pessimistic L and optimistic U bounds are comprehensively detailed in Appendix B).

**Table 4** Initial vs. optimal targets for all 14 branches at middle bound (M)

| DMU   | I1_In<br>it | I1_Targ<br>et | I2_In<br>it | I2_Targ<br>et | I3_In<br>it | I3_Targ<br>et | O1_In<br>it | O1_Targ<br>et | O2_In<br>it | O2_Targ<br>et | O3_In<br>it | O3_Targ<br>et |
|-------|-------------|---------------|-------------|---------------|-------------|---------------|-------------|---------------|-------------|---------------|-------------|---------------|
| DMU1  | 8           | 8.47          | 135         | 341.96        | 3115        | 13148.5       | 41705       | 58059.5       | 16140       | 248259.       | 1131        | 6769.85       |
| DMU2  | 11          | 6             | 535         | 240           | 2084        | 4715          | 47089       | 37849         | 45097       | 192622        | 10107       | 3779          |
| DMU3  | 13          | 6             | 542         | 240           | 6102        | 4715          | 62469       | 37849         | 38018       | 192622        | 3673        | 3779          |
| DMU4  | 8           | 6             | 295         | 240           | 4244        | 4715          | 38308       | 37849         | 24983       | 192622        | 2406        | 3779          |
| DMU5  | 7           | 5             | 392         | 124           | 2469        | 13766         | 25042       | 23742         | 17616       | 165422        | 2231        | 3406          |
| DMU6  | 13          | 6             | 627         | 240           | 1234        | 4715          | 10293       | 37849         | 35659       | 192622        | 11169       | 3779          |
| DMU7  | 5           | 7             | 124         | 274           | 1376        | 731           | 23742       | 42361         | 16542       | 250478        | 3406        | 0             |
| DMU8  | 6           | 10.33         | 240         | 489.78        | 4715        | 9790.16       | 37849       | 77667.3       | 19262       | 280655.       | 3779        | 8255.2        |
| DMU9  | 7           | 7             | 320         | 274           | 1428        | 731           | 44825       | 42361         | 25176       | 250478        | 1357        | 0             |
| DMU10 | 4           | 5             | 165         | 124           | 3753        | 13766         | 17856       | 23742         | 10093       | 165422        | 1359        | 3406          |
| DMU11 | 5           | 7             | 466         | 274           | 4802        | 731           | 25911       | 42361         | 16679       | 250478        | 2859        | 0             |
| DMU12 | 6           | 13            | 552         | 627           | 4015        | 12341         | 30402       | 102939        | 17464       | 356593        | 3024        | 11169         |
| DMU13 | 7           | 6.21          | 274         | 263.93        | 731         | 3044.88       | 42361       | 33870.7       | 25047       | 199171.       | 0           | 1748.61       |
| DMU14 | 6           | 13            | 411         | 627           | 6112        | 12341         | 26304       | 102939        | 21623       | 356593        | 2828        | 11169         |

Note: In the table headers, the \_Init and \_Target suffixes represent the initial observed values and the optimal projected values recommended by the model, respectively. Also, Decimal values represent continuous scale adjustments; fractional workforce targets (e.g.,  $I_1$  for DMU1 = 8.47) can be practically interpreted in terms of working hours or part-time staff allocations.

A deeper analysis of the results outlined in Table 4 reveals three distinct operational strategies prescribed by the optimization model: Expansion, Contraction, and Specialization/Consolidation.

1. Strategic Expansion (e.g., DMU1, DMU8, DMU12, DMU14):

Several branches are identified as highly capable hubs that should absorb excess demand and operational weight. For instance, DMU12 and DMU14 are designated to more than double their workforce ( $I_1$  from 6 to 13). Similarly, DMU1 is instructed to expand its physical capacity ( $I_2$ ) from 135 to 341.96 square meters and increase its activity rate ( $O_3$ ) nearly six-fold (from 1,131

to 6,769.85). This indicates that the system benefits most when these specific nodes process a larger share of the banking network's total workflow.

## 2. Downsizing and Resource Extraction (e.g., DMU2, DMU3, DMU6):

Conversely, some historically oversized branches are slated for significant reduction. DMU6, which initially operated with 13 personnel and a vast physical space of 627 sq.m, is targeted to scale down to 6 personnel and 240 sq.m. The centralized model detects that the inputs consumed by these branches yield better marginal returns when reallocated to branches like DMU8 or DMU12.

## 3. Task Specialization and Consolidation (e.g., DMU7, DMU9, DMU11, DMU13):

Perhaps the most compelling finding of the CDEA model is its inclination towards structural reorganization rather than mere proportional scaling. For DMU7, DMU9, and DMU11, the optimal target for the activity rate/service provision ( $O_3$ ) is reduced to precisely 0.00. In banking terms, this implies that certain specific services or localized activities should be completely halted at these branches and centralized elsewhere to eliminate redundancies. Interestingly, DMU13, which initially generated an  $O_3$  value of 0, is now targeted to produce 1,748.61 units of this output, suggesting it should be newly assigned an operational role previously handled by other branches.

In summary, the optimal targets demonstrate that achieving systemic efficiency requires breaking away from homogeneous operations. The model directs management to tailor the size and functional scope of each branch according to its comparative advantage within the network.

## 4.5 Managerial implications and practical considerations

The application of the lexicographic FFCDEA model provides bank management with a rigorous blueprint for systemic optimization. However, translating these mathematical targets into real-world banking operations requires a nuanced approach, particularly regarding the inherent "liquidity" or transferability of different resources. Reviewers and practitioners might rightly question the physical feasibility of seamlessly reallocating certain inputs and outputs across the network.

To operationalize the findings derived in Section 4.4, management must categorize the prescribed targets into short-term tactical adjustments and long-term strategic initiatives:

### 1. Reallocation of Fluid Resources (Short-to-Medium Term):

Targets related to the workforce ( $I_1$ ), operational expenses ( $O_2$ ), and institutional resources ( $O_1$ ) represent fluid assets that can be dynamically managed. For instance, the model's directive to reduce the workforce in DMU2 and DMU3 while doubling it in DMU12 and DMU14 can be pragmatically executed through staff redeployment programs, altering hiring freezes, or offering geographic transfer incentives. Similarly, adjusting operational budgets ( $O_2$ ) is entirely within the immediate purview of the central financial committee.

### 2. Management of Fixed Assets and Physical Space (Long-Term Strategy):

The most critical practical challenge in implementing CDEA targets lies in fixed assets, specifically the physical space ( $I_2$ ). Unlike human capital, physical square footage cannot be physically detached from one branch and appended to another. When the model dictates a contraction in physical space for a branch (e.g., DMU6 shrinking from 627 to 240 sq.m), it strategically signals an over-investment in real estate relative to the branch's productive output. In practice, management should interpret these targets as guidelines for a Corporate Real Estate Portfolio Strategy. The excess capacity can be addressed by:

**Subleasing or Repurposing:** Unused physical space in oversized branches can be leased out to third parties or repurposed into centralized, non-client-facing administrative hubs (e.g., IT data centers, regional archive rooms) that do not count towards the branch's direct operational inputs.

**Relocation and Capital Expenditure:** For branches requiring massive spatial expansion (e.g., DMU1 and DMU8), the targets mathematically justify the capital expenditure required to relocate the branch to a larger facility within the same commercial district, or to acquire adjacent properties.

### 3. Redirecting Client Demand ( $I_3$ ) and Activity Specialization ( $O_3$ ):

Client demand ( $I_3$ ) is tied to demographic and regional factors. To shift demand away from downsized branches and towards expanded operational hubs, the central management must employ zoning policies. This involves restructuring the geographic coverage areas of specific branches, redirecting corporate client accounts to designated hubs (like DMU12 and DMU14), and employing digital banking incentives to decouple demand from physical footfall. Furthermore, as observed in the model's recommendation to reduce the activity rate ( $O_3$ ) to zero in DMU7, DMU9, and DMU11, management is advised to establish Specialized Service Hubs. Instead of every branch offering every service (e.g., foreign exchange, large-scale corporate loans), redundant services should be phased out in smaller branches and centralized in the expanded units.

Ultimately, the FFCDEA targets should not be viewed as an overnight restructuring mandate, but rather as an evidence-based roadmap. It provides the central authority of the Refah Kargaran Bank with the precise mathematical justification needed to guide multi-year strategic planning, property acquisition, and corporate restructuring under uncertain conditions.

## 5 Conclusion and future research directions

### 5.1. Conclusion

This study addressed the complex challenge of resource allocation and target setting in organizational networks operating under high uncertainty. We proposed a Fully Fuzzy Centralized DEA model under the VRS assumption. Unlike traditional DEA models that evaluate units independently, our centralized approach optimized the performance of the entire system (macro-level) while simultaneously determining the most efficient targets for individual DMUs (micro-level). To solve the proposed fully fuzzy model, a rigorous three-stage lexicographic approach combined with the C-C transformation was employed, ensuring computationally tractable and mathematically sound solutions.

The practical applicability of the proposed approach was demonstrated through a real-world numerical example involving 14 bank branches. By modeling inputs and outputs as TFNs, the study successfully captured the inherent ambiguity in banking operations, such as fluctuating customer demands and unquantifiable service qualities. The findings revealed that systemic efficiency can be achieved through strategic resource reallocation—specifically, by downsizing underutilized inputs (e.g., physical infrastructure) and expanding operational outputs. Furthermore, the analysis provided actionable managerial insights by categorizing branches into candidates for expansion, downsizing, or consolidation, while taking into account the practical limitations of resource liquidity (e.g., the inflexibility of physical spaces).

## 5.2. Future research directions

While the proposed FFCDEA model provides a robust framework for performance evaluation under uncertainty, several promising avenues for future research can be identified:

1. **Network and Dynamic DEA:** The current model treats each DMU as a "black box." Future studies could extend this approach to a Network DEA framework to examine the internal operational stages of bank branches (e.g., deposit generation vs. loan allocation). Additionally, incorporating Dynamic DEA would allow for the evaluation of centralized target setting over multiple time periods.
2. **Inclusion of Undesirable Outputs:** In the banking sector, operations often generate undesirable outputs, such as Non-Performing Loans (NPLs) or customer complaints. Integrating undesirable outputs into the fully fuzzy centralized model would provide a more comprehensive and realistic assessment of bank performance.
3. **Alternative Uncertainty Approaches:** While this study utilized TFNs, future research could explore other advanced uncertainty modeling techniques, such as Type-2 Fuzzy Sets, Intuitionistic Fuzzy Sets, or Robust Optimization methodologies, to compare their effectiveness in handling highly volatile data.
4. **Weight Restrictions and Preferences:** Incorporating weight restrictions or decision-maker preferences (e.g., using the Analytic Hierarchy Process or Delphi method) into the objective function could align the systemic targets more closely with the strategic priorities of the central management.

## References

1. Farrell, M. J., (1957). The measurement of productive efficiency. *J. R. Stat. Soc. Ser., A* 120, 253–281.
2. Charnes, A., Cooper, W. W., Rhodes, E., (1978). Measuring the efficiency of decision-making units. *Eur. J. Opt. Res.*, 2, 429–444.
3. Golany, B., Phillips, F. Y., Rousseau, J. J., (1993). Models for improved efficiency results. *IIE Transactions*, 25(6), 2–10.
4. Athanassopoulos, A. D., (1995). Goal programming of data envelopment analysis (GoDEA) for target-based multi-level planning. *European Journal of Operational Research*, 87, 535–550.
5. Lozano, S., Villa, G., (2004). Centralized resource allocation using data envelopment analysis. *Journal of Productivity Analysis*, 22, 143–161.
6. Lozano, S., Villa, G., (2005). Centralized DEA models with the possibility of downsizing. *Journal of the Operational Research Society*, 56(4), 357–364.
7. Asmild, M., Paradi, J. C., Pastor, J. T., (2009). Centralized resource allocation BCC models. *Omega*, 37, 40–49.
8. Hosseinzadeh Lotfi, F., Noora, A. A., Jahanshahloo, G. R., Gerami, J., Mozaffari, M. R., (2010). Centralized resource allocation for enhanced Russell models. *Journal of Computational and Applied Mathematics*, 235(1), 1–10.
9. Cecilio, M. M., Prior, D., Segovia, M. M., Portillo, F., (2014). On centralized resource utilization and its reallocation by using DEA. *Annals of Operations Research*, 214, 87–105.
10. Feng, L., (2014). Centralized resource allocation based on efficiency analysis for step-by-step improvement paths. *Omega*, 51, 24–33.
11. Hakim, S., Seifi, A., Ghaemi, A., (2016). A bi-level formulation for DEA-based centralized resource allocation under efficiency constraints. *Computers and Industrial Engineering*, 93, 28–35.
12. Sadeghi, J., Dehnohalaji, A., (2019). A comprehensive method for the centralized resource allocation in DEA. *Computers & Industrial Engineering*, 127, 344–352.
13. Arocena, P., Cabasés, F., Pascual, P., (2022). A centralized directional distance model for efficient and horizontally equitable grants allocation to local governments. *Socio-Economic Planning Sciences*, 81, 100947.

14. Soofizadeh, S., Fallahnejad, R., (2021). Identifying the effective factors in banking sector using data envelopment analysis considering system efficiency. *Advances in Mathematical Finance and Applications*, 6(4), 743-760.
15. Bellman, R. E., Zadeh, L. A., (1970). Decision-making in a fuzzy environment. *Management Science*, 17(B), 141-164.
16. Sengupta, J. K., (1992). A fuzzy systems approach in data envelopment analysis. *Computers and Mathematics with Applications*, 24, 259-266.
17. Zimmermann, H. J., (1976). Description and optimization of fuzzy system. *International Journal of General System*, 2, 209-216.
18. Kao, C., Liu, S. T., (2000). Fuzzy efficiency measures in data envelopment analysis. *Fuzzy Sets and Systems*, 119, 149-160.
19. Wang, Y. M., Chin, K. S., (2011). Fuzzy data envelopment analysis: A fuzzy expected value approach. *Expert Systems with Applications*, 37, 11678-11685.
20. Wang, Y. M., Luo, Y., Liang, L., (2009). Fuzzy data envelopment analysis based upon fuzzy arithmetic. *Expert Systems with Applications*, 36, 5205-5211.
21. Wen, M., You, C., Kang, R., (2010). A new ranking method to fuzzy data envelopment analysis. *Computers & Mathematics with Applications*, 59, 3398-3404.
22. Hosseinzadeh Lotfi, F., Jahanshahloo, G. R., Alimardani, M., (2007). A new approach for efficiency measures by fuzzy linear programming. *Applied Mathematical Sciences*, 14, 647-663.
23. Maleki, H. R., (2002). Ranking functions and their applications to fuzzy linear programming. *Far East Journal of Mathematical Sciences*, 4, 283-301.
24. Saati, S., Memariani, A., (2005). Reducing weight flexibility in fuzzy DEA. *Applied Mathematics and Computation*, 161, 611-622.
25. Liu, S. T., (2008). A fuzzy DEA/AR approach to the selection of flexible manufacturing system. *Computer and Industrial Engineering*, 54, 66-76.
26. Hatami-Marbini, A., Saati, S., Sajadi, S. M., (2018). Efficiency analysis in two-stage structures using fuzzy data envelopment analysis. *Central European Journal of Operations Research*, 26, 35-54.
27. Tabatabaei, S., Mozaffari, M. R., Rostamy-Malkhalifeh, M., (2022). Fuzzy efficiency evaluation in relational network data envelopment analysis. *Complex & Intelligent Systems*, 8, 3959-3977.
28. Zhou, S. J., Zhang, Z. D., Li, Y. C., (2008). Research of real estate investment risk evaluation based on fuzzy data envelopment analysis method. *Proc. of Int. Conf. on Risk Management*, 444-448.
29. Koohathongsumrit, N., Meethom, W., (2021). An integrated approach of fuzzy risk assessment model and data envelopment analysis. *Expert Systems with Applications*, 171, 114342.
30. Izadikhah, M., (2022). A fuzzy stochastic slacks-based data envelopment analysis model with application to healthcare efficiency. *Healthcare Analytics*, 2, 100038.
31. Wang, S., Lei, L., Xing, L., (2021). Urban circular economy performance evaluation: A novel fully fuzzy data envelopment analysis. *Journal of Cleaner Production*, 324, 129214.
32. Soofizadeh, S., Fallahnejad, R., (2023). Evaluation of groups using cooperative game with fuzzy data envelopment analysis. *AIMS Mathematics*, 8(4), 8661-8679.
33. Saini, N., Gandotra, N., Bajaj, R. K., Dwivedi, R. P., (2020). Ranking of decision-making units in Pythagorean fuzzy CCR model. *Materials Today: Proceedings*, 28, 41-46.
34. Hatami-Marbini, A., Ebrahimnejad, A., Lozano, S., (2017). Fuzzy efficiency measures in data envelopment analysis using lexicographic multi objective approach. *Computers & Industrial Engineering*, 105, 362-376.
35. Pourahmad, S., Jahanshahloo, G. R., (2022). Centralized resource allocation in network DEA under uncertainty. *Expert Systems with Applications*, 188, 116060.
36. Liu, Y., Zhang, J., (2025). Robust-fuzzy hybrid DEA for uncertain centralized systems. *Expert Systems with Applications*.
37. Li, X., Chen, Y., (2023). Lexicographic multi-objective optimization for fuzzy efficiency analysis. *Applied Soft Computing*, 136, 110155.
38. Zhao, P., Du, J., (2024). Fully fuzzy multi-objective linear programming for uncertain efficiency analysis. *Soft Computing*.
39. Charnes, A., Cooper, W. W., (1962). Programming with linear fractional functionals. *Naval Research Logistics Quarterly*, 9, 181-186.
40. Fallahnejad, R., (2018). Technically efficient targets for the groups by using the centralized scenario and enhanced Russell measure. *International Journal of Data Envelopment Analysis*, 6, 1461-1480.



## Appendix A: Notation and Symbols

This appendix summarizes the indices, parameters, variables, and abbreviations used throughout the paper. Providing this notation table facilitates the understanding of the mathematical formulations presented in the modeling section.

| Symbol<br>/Abbreviation         | Description                                                                                   |
|---------------------------------|-----------------------------------------------------------------------------------------------|
| Abbreviation                    |                                                                                               |
| DEA                             | Data Envelopment Analysis                                                                     |
| DMU                             | Decision-Making Unit                                                                          |
| CDEA                            | Centralized Data Envelopment Analysis                                                         |
| FDEA                            | Fuzzy Data Envelopment Analysis                                                               |
| ERM                             | Enhanced Russell Measure                                                                      |
| MOFP                            | Multi-Objective Fractional Programming                                                        |
| LP                              | Linear Programming                                                                            |
| C-C                             | Charnes-Cooper transformation                                                                 |
| CRS                             | Constant Returns to Scale                                                                     |
| CDM                             | Centralized Decision Maker                                                                    |
| Index                           |                                                                                               |
| $i$                             | Index for inputs $i = 1 \dots m$                                                              |
| $k$                             | Index for outputs $k = 1 \dots s$                                                             |
| $j$                             | Index for Decision-Making Units $j = 1 \dots n$                                               |
| $r$                             | Index for the target DMU in resource allocation models                                        |
| $p$                             | Index for the evaluated DMU in the ERM model                                                  |
| $f$                             | Index for triangular fuzzy number components (Lower Middle Upper bounds)                      |
| Parameter / Variable            |                                                                                               |
| $\widehat{x\hat{y}}$            | Virtual targets (projected points) for inputs and outputs on the strong frontier based on ERM |
| $u$                             | Positive scalar variable introduced in the C-C transformation                                 |
| $\varepsilon$                   | Non-Archimedean infinitesimal value for strict positivity constraints                         |
| $\tilde{\theta}$                | Optimal fuzzy contraction factor for total input resources across the centralized system      |
| $\tilde{\Phi}$                  | Optimal fuzzy expansion factor for total output productions across the centralized system     |
| $\widetilde{X_1^{sys\ target}}$ | Overall optimal fuzzy target level for the total consumption of resource $i$                  |
| $\widetilde{Y_k^{sys\ target}}$ | Overall optimal fuzzy target level for the total generation of output $k$                     |
| $\lambda_{jr}$                  | Intensity variable dictating the reallocation weight of DMU $j$ for DMU $r$                   |
| $\widetilde{x_{1r}^{target}}$   | Optimal fuzzy input allocation target for a specific DMU $r$                                  |
| $\widetilde{y_{kr}^{target}}$   | Optimal fuzzy output target for a specific DMU $r$                                            |

## Appendix B: Lower and Upper Bound Results of the FFCDEA Model

This appendix provides supplementary data and computational results for the lower (\$L\$) and upper (\$U\$) bounds of the triangular fuzzy numbers used in the proposed FFCDEA model under the Variable Returns to Scale (VRS) assumption.

While Section 4 focuses primarily on the most plausible middle level (\$M\$) to facilitate clear managerial insights and practical analysis, Tables B.1 and B.2 present the complete initial and target values for all inputs (\$I\_1, I\_2, I\_3\$) and outputs (\$O\_1, O\_2, O\_3\$) across the 14 Decision Making Units (DMUs) at the \$L\$ and \$U\$ levels, respectively. Providing these extreme bounds offers a comprehensive view of the uncertainty margins and the full spectrum of optimal resource allocation scenarios for each bank branch.

**Table B.1** Initial and optimal target values of inputs and outputs for the 14 bank branches at the lower bound

| DM<br>U   | I1_In<br>it L | I1_Tar<br>get L | I2_In<br>it L | I2_Tar<br>get L | I3_In<br>it L | I3_Tar<br>get L | O1_I<br>nit L | O1_Tar<br>get L | O2_I<br>nit L | O2_Tar<br>get L | O3_I<br>nit L | O3_Tar<br>get L |
|-----------|---------------|-----------------|---------------|-----------------|---------------|-----------------|---------------|-----------------|---------------|-----------------|---------------|-----------------|
| DM<br>U1  | 4             | 4.73            | 121           | 259.03          | 1246          | 7599.4          | 1668          | 52253.          | 1129          | 179859          | 565           | 3770.6          |
| DM<br>U2  | 7             | 4               | 428           | 96              | 1042          | 2357            | 4238          | 30279           | 3156          | 154097          | 5053          | 2645            |
| DM<br>U3  | 11            | 4               | 433           | 96              | 2440          | 2357            | 4997          | 30279           | 1520          | 154097          | 2203          | 2645            |
| DM<br>U4  | 4             | 4               | 206           | 96              | 2970          | 2357            | 3447          | 30279           | 9993          | 154097          | 1684          | 2645            |
| DM<br>U5  | 5             | 3               | 156           | 74              | 1234          | 9636            | 1752          | 21367           | 1409          | 99253           | 1338          | 2384            |
| DM<br>U6  | 7             | 4               | 501           | 96              | 4936          | 2357            | 9264          | 30279           | 2852          | 154097          | 5584          | 2645            |
| DM<br>U7  | 3             | 4               | 74            | 246             | 9636          | 584             | 2136          | 21180           | 9925          | 225430          | 2384          | 0               |
| DM<br>U8  | 4             | 5.51            | 96            | 391.40          | 2357          | 3915.7          | 3027          | 69900.          | 1540          | 227521          | 2645          | 4086.7          |
| DM<br>U9  | 6             | 4               | 288           | 246             | 7142          | 584             | 2241          | 21180           | 1510          | 225430          | 542           | 0               |
| DM<br>U10 | 2             | 3               | 132           | 74              | 1501          | 9636            | 1607          | 21367           | 9083          | 99253           | 543           | 2384            |
| DM<br>U11 | 3             | 4               | 279           | 246             | 2401          | 584             | 1295          | 21180           | 1501          | 225430          | 2001          | 0               |
| DM<br>U12 | 4             | 7               | 496           | 501             | 1606          | 4936            | 2432          | 92645           | 1571          | 285274          | 2116          | 5584            |
| DM<br>U13 | 4             | 3.78            | 246           | 176.89          | 584           | 1526.8          | 2118          | 22352.          | 2254          | 170109          | 0             | 1062.0          |
| DM<br>U14 | 4             | 7               | 164           | 501             | 4889          | 4936            | 1315          | 92645           | 1729          | 285274          | 1979          | 5584            |

**Table B.2** Initial and optimal target values of inputs and outputs for the 14 bank branches at the upper bound.

| DM<br>U   | I1_In<br>it U | I1_Tar<br>get U | I2_In<br>it U | I2_Tar<br>get U | I3_In<br>it U | I3_Tar<br>get U | O1_I<br>nit U | O1_Tar<br>get U | O2_I<br>nit U | O2_Tar<br>get U | O3_I<br>nit U | O3_Tar<br>get U |
|-----------|---------------|-----------------|---------------|-----------------|---------------|-----------------|---------------|-----------------|---------------|-----------------|---------------|-----------------|
| DM<br>U1  | 14            | 12.20           | 216           | 478.06          | 5295          | 20546.          | 79239         | 92470.          | 27439         | 391137          | 1583          | 11217.          |
| DM<br>U2  | 15            | 11              | 963           | 408             | 3544          | 8015            | 65924         | 56773           | 63135         | 327457          | 14149         | 7180            |
| DM<br>U3  | 20            | 11              | 758           | 408             | 8542          | 8015            | 11869         | 56773           | 60829         | 327457          | 6244          | 7180            |
| DM<br>U4  | 15            | 11              | 472           | 408             | 6366          | 8015            | 57462         | 56773           | 37475         | 327457          | 4330          | 7180            |
| DM<br>U5  | 9             | 7               | 548           | 173             | 3950          | 19272           | 37563         | 45109           | 26424         | 281217          | 3123          | 6130            |
| DM<br>U6  | 19            | 11              | 877           | 408             | 2221          | 8015            | 15440         | 56773           | 53488         | 327457          | 17870         | 7180            |
| DM<br>U7  | 7             | 12              | 173           | 520             | 1927          | 1388            | 45109         | 76249           | 28121         | 425812          | 6130          | 0               |
| DM<br>U8  | 11            | 15.44           | 408           | 685.12          | 8015          | 17175.          | 56773         | 117561          | 32745         | 420982          | 7180          | 13207.          |
| DM<br>U9  | 13            | 12              | 448           | 520             | 2142          | 1388            | 71720         | 76249           | 45316         | 425812          | 1899          | 0               |
| DM<br>U10 | 7             | 7               | 231           | 173             | 5254          | 19272           | 30355         | 45109           | 15139         | 281217          | 2174          | 6130            |
| DM<br>U11 | 9             | 12              | 838           | 520             | 9123          | 1388            | 41457         | 76249           | 30023         | 425812          | 4288          | 0               |
| DM<br>U12 | 9             | 19              | 772           | 877             | 6424          | 22213           | 42562         | 154408          | 26196         | 534889          | 5745          | 17870           |
| DM<br>U13 | 12            | 10.36           | 520           | 444.69          | 1388          | 4960.8          | 76249         | 56354.          | 42581         | 326599          | 0             | 2974.1          |
| DM<br>U14 | 10            | 19              | 657           | 877             | 9168          | 22213           | 44716         | 154408          | 41084         | 534889          | 4807          | 17870           |